

New Product Introduction

i-NVR

- High-performance Intelligent Network Video Recorder
- Compatible with:
 - C-series codecs
 - S-series video servers
 - OpteliDome™ and OpteliCam™ IP-cameras
 - Third-party IP-cameras
- Reliable video storage and easy retrieval
- JBOD (Compact) or RAID5 (Elite)
- Intelligent video motion detection
- Industrial designed for 24/7 operation
- Lip-sync audio support**
- SDK support



The *i-NVR* Compact and Elite series complement Optelecom-NKF's IP surveillance portfolio with a cost-effective, reliable video storage solution. The *i-NVR* is an essential part of a video surveillance application for storing and retrieving vital video information. The *i-NVR* is operated using its own MMI, Operator Office™, or by using MX™ SDK (Software Development Kit). The *i-NVR* supports video streams from the S- and C-series video codecs/servers, OpteliDome™ and OpteliCam™ IP-cameras. (For compatibility with other IP-cameras, please contact Optelecom-NKF.)

Storage and retrieval

The *i-NVR* Compact supports scheduled background recording in a FIFO cyclic buffer, and alarm track recording with configurable pre- and post-event duration. Tracks can be retrieved and exported to CD-ROM or DVD, based on camera name, time/date, event and user-definable bookmarks. The exported

files are watermarked with a checksum to ensure content integrity. The *i-NVR* can simultaneously handle background recording of 16 to 64 streams, (live) viewing of 6 or more cameras, and event-driven recording while executing all management tasks.

Robust, reliable design

The mechanical housing is a 2U or 4U industrial 19" housing. All high-grade mechanical and electrical components are selected for their reliability and performance for 24/7 operation.

Versatile CCTV solutions

The *i-NVR* is a component of Optelecom-NKF's Siquira™ surveillance solutions; seamless integration of video management, network recording, client and control software, and video content analysis software.

Model

Description


i-NVR Compact Series

Compact 16- or 32 channel *i-NVR*, 2U 19" rack-mountable or standalone housing

i-NVR Elite Series

32- or 64 channel hot swappable RAID-5 *i-NVR*, 2 or 4U 19" rack housing

** : Not yet available.



Video

Nr of input streams	16, 32 or 64	
Device/stream compatibility	C-series encoders and decoders S-series video servers and decoders OpteliDome series IP cameras (For other vendors, contact Optelecom-NKF)	
Resolution (HxV)	PAL	NTSC
D1	720x576	720x480
2/3D1	480x576	480x480
HD1	352x576	352x480
CIF	352x288	352x240
QCIF	176x144	176x120
Frame rate	1 to 25/30 fps, configurable per stream	

Security

Authorization	Multilevel password protection
Logging	User activity
Image authentication	Checksum
Source authentication	Audit trail in stream

Software

Operating system	Windows XP professional
Graphical user interface	Comprehensive, intuitive GUI included (Compact only)

Events/ scheduling

Event triggers	Intelligent Video Motion Detection External Alarm/Event triggers from encoders/servers/cameras (Contact Closures, VMD) Optional Intelligent Scene Analysis (ISAS) Optional Automatic Number Plate Recognition (ANPR)
Transmission	10/100/1000GB Ethernet
Export/import media	CD/DVD writer/player USB memory stick

Network Management & Control

Management/ configuration	MX™ Configuration Toolkit 2.0 and higher; MX™ SDK 1.4 and higher.
---------------------------	---

Powering

Power supply	230 Vac (/EU) or 115 Vac (/US)
--------------	--------------------------------

Environmental

Operating temperature	0 to 40 °C
Recommended temp. range	+10 to +30 °C
Relative humidity	< 90% (no condensation)

Mechanical

Dimensions	2U or 4U 19" rack
------------	-------------------

www.sigura.com
www.optelecom-nkf.com

Optelecom-NKF, Inc. USA

Telephone +1 301.444.2200
E-mail sales.us@optelecom-nkf.com

Optelecom-NKF United Kingdom

Telephone +44 1204 546 635
E-mail sales.uk@optelecom-nkf.com

Optelecom-NKF Singapore

Telephone +65 6264 7501
E-mail sales.sg@optelecom-nkf.com

Optelecom-NKF B.V. The Netherlands

Telephone +31 182 592 333
E-mail sales.nl@optelecom-nkf.com

Optelecom-NKF S.L. Spain

Telephone +34 91 676 8164
E-mail sales.es@optelecom-nkf.com

Optelecom-NKF S.A.S. France

Telephone +33 1 47 66 88 65
E-mail sales.fr@optelecom-nkf.com