

Product information



NVR-216
NVR-208
NVR-204
NVR-202

- 16-channel Mini Network Video Recorder
- 8-channel Mini Network Video Recorder
- 4-channel Mini Network Video Recorder
- 2-channel Mini Network Video Recorder

Features

- Dual stream for managing bandwidth
- Support of iPhone, iPad, Android, BlackBerry mobile clients
- Web-based live viewer / playback
- Online GUI recording schedule
- Up to 4 (NVR-216/208) / 2 (NVR-204/202) SATA HDD
- RAID 0, 1, 5, 10 (NVR-216/208) / 0, 1 (NVR-204/204)
- Digital PTZ and multi-view
- Audio support
- Real-time digital output and email alert
- Up to 64 channels remote live view
- Playback with 5 intelligent search functions
- Digital watermark
- Supported by NUUO Central Management System

Technical data

	NVR-216	NVR-208	NVR-204	NVR-202
IP video channels	1-16	1-8	1-4	1-2
Number of drives	4 x SATA II		2 x SATA II	
RAID level	RAID 0, 1, 5, 10		RAID 0, 1	
I/O interface	2 x USB 2.0, 1 x eSATA (function reserved)		2 x USB 2.0	
LAN port	2 x Gigabit RJ-45 Ethernet port		1 x Gigabit RJ-45 Ethernet port	
Compression format	MPEG4, M-JPEG, H.264, MxPEG (depends on IP camera)			
Recording performance	camera dependent, total bitrate in/out: 80 Mbps		camera dependent, total bitrate in/out: 40 Mbps	
Remote PC CPU	min. Intel Core 2 Duo, 2,6 GHz			
Remote PC RAM	min. 1 GB			
User interface	HTTP web browser – Internet Explorer 7 and higher / PC client application programme			
Recording type	continuous recording, schedule recording, manual recording, event recording, digital input trigger recording			
Remote live view control	live view, preset / go, PTZ, remote I/O, snapshot, multi-view, digital PTZ, advanced E-Map, bandwidth monitoring			
Audio & video recording	audio & video recording in synchronization			
Auto backup	automatic backup of the recorded video of the previous date to FTP			
Smart search	general motion, missing object, foreign object, lose focus, camera occlusion			
Remote client OS platform	Windows XP (32-bit) / Vista (32-bit) / 7 (32 and 64-bit)			
Remote live view connections	live view maximum 64 connections at the same time			
Mobile client OS platform	iPhone, iPad, Android, BlackBerry			
Power source	19 V DC, 110/230 V AC via included power supply			
Power consumption	40 W max.			
Ambient temperature	0°C ~ +40°C			
Humidity	10% ~ 85%			
Dimensions (WxHxD)	110 x 150 x 202 mm			
Weight	2,1 kg (w/o HDD)			

Ordering information

NVR-216 NH	16-channel Mini Network Video Recorder, w/o storage HDD, 19 V DC (110/230 V AC power supply included)
NVR-208 NH	8-channel Mini Network Video Recorder, w/o storage HDD, 19 V DC (110/230 V AC power supply included)
NVR-204 NH	4-channel Mini Network Video Recorder, w/o storage HDD, 19 V DC (110/230 V AC power supply included)
NVR-202 NH	2-channel Mini Network Video Recorder, w/o storage HDD, 19 V DC (110/230 V AC power supply included)

NVR_216_208_204_202_db_en_rev01