

VIDEO MONITOR RANGE

VMC-7314P VMC-7321P
VMC-7325P VMC-7328P



Suitable for CCTV, retail and public display applications, these high quality, plastic case monitors are designed specifically for commercial installations.

Manufactured in the UK, they combine unbeatable reliability with a range of features guaranteed to meet the most demanding requirements.

Main Features

- 14", 21", 25" and 28" screen sizes
- No tuner, so no TV licence required
- Professional BNC connections (in/out)
- Amplified signal loop through (up to 8 sets)
- 400 TVL resolution
- Tough plastic casing

SANYO

VIDEO MONITOR RANGE



VMC-7314P
VMC-7321P
VMC-7325P
VMC-7328P

SPECIFICATIONS

Model Number	VMC-7314P
Screen Size	14" (v34cm)
Screen Deflection	90°
Resolution	400 TVL
Scanning Frequency	15.625kHz/50Hz or 15.750/60Hz (H/V)
Audio System	Mono 1.5W RMS
Terminals	BNC video x 2 (in/out), RCA audio x 2 (in/out)
Front Panel Controls	Brightness/Colour/Contrast/Sharpness/Volume
Remote Operation	No
User Control	on-screen display
Power	AC 220-240V, 50Hz
Dimensions	370 x 336.5 x 379 (W x H x Dmm)
Net Weight	8.6kg

Model Number	VMC-7321P
Screen Size	21" (v51cm)
Screen Deflection	90°
Resolution	400 TVL
Scanning Frequency	15.625kHz/50Hz or 15.750/60Hz (H/V)
Audio System	Mono 1.5W RMS
Terminals	BNC video x 2 (in/out), RCA audio x 2 (in/out)
Front Panel Controls	Brightness/Colour/Contrast/Sharpness/Volume
Remote Operation	No
User Control	Colour on-screen display
Power	AC 220-240V, 50Hz
Dimensions	514 x 466 x 482 (W x H x Dmm)
Net Weight	19.4kg

Model Number	VMC-7325P
Screen Size	25" (v59cm)
Screen Deflection	90°
Resolution	400 TVL
Scanning Frequency	15.625kHz/50Hz (H/V)
Audio System	Mono 2.0W RMS
Terminals	BNC video x 2 (in/out), RCA audio x 2 (in/out)
Front Panel Controls	Brightness/Colour/Contrast/Sharpness/Volume
Remote Operation	Yes, via optional remote (JXMCC)
User Control	Colour on-screen display
Power	AC 220-240V, 50Hz
Dimensions	584 x 534 x 447 (W x H x Dmm)
Net Weight	24.5kg

Model Number	VMC-7328P
Screen Size	28" (v66cm)
Screen Deflection	90°
Resolution	400 TVL
Scanning Frequency	15.625kHz/50Hz (H/V)
Audio System	Mono 2.0W RMS
Terminals	BNC video x 2 (in/out), RCA audio x 2 (in/out)
Front Panel Controls	Brightness/Colour/Contrast/Sharpness/Volume
Remote Operation	Yes, via optional remote (JXMKE)
User Control	Colour on-screen display
Power	AC 220-240V, 50Hz
Dimensions	628 x 567 x 469 (W x H x Dmm)
Net Weight	30.4kg

v = visible area

Installer:

SANYO

Commercial Division. SANYO Europe Ltd, SANYO House,
Otterspool Way, Watford, Herts WD25 8JX
Telephone: 01923 477220 Fax: 01923 477225 www.sanyo.co.uk

Whilst every care is taken to ensure that the details in this leaflet are correct at the time of going to press, they are intended as a guide only and do not constitute an offer. Because SANYO'S policy is one of continuous improvement, it is possible that alterations to specifications may have occurred since printing. For clarification on any point, please contact your local appointed dealer, or write to SANYO at the address shown.